

SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: BF C&B Alloy
Product Number: 0401K, 0401S, 0401-250

Company Identification

Nobilium Company, Division of CMP Industries LLC
413 North Pearl St
Albany, NY 12207-1311 USA
(518)-434-3147 (For product information)
(800)-424-9300 (For emergencies)

2. HAZARDS IDENTIFICATION

```
***** EMERGENCY OVERVIEW *****
*
* Cancer hazard. Dust or vapor extremely irritating
* to eyes and respiratory tract.
*
*****
```

NFPA Rating - Health:
Flammability:
Reactivity:
Special Hazard: N/A

EYE:
Causes eye irritation.

SKIN:
Can cause moderate skin irritation. Allergic reactions are possible.

INHALATION:
Dust may be slightly irritating to respiratory tract.

INGESTION:
Ingestion is not considered a potential route of exposure.



(section 2 continued)

CHRONIC EFFECTS:

Respiratory Disease may result due to long term exposure.

REPRODUCTIVE HAZARDS:

None.

CARCINOGENICITY INFORMATION:

Cancer hazard (contains material which) can cause cancer. Listed by IARC and NTP as a carcinogen.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

<u>Chemical Name</u>	<u>Amount</u>	<u>CAS Number</u>
NICKEL	77.0 %	7440-02-0
CHROMIUM	11.5 %	7440-47-3
MOLYBDENUM	3.5 %	7439-98-7
COLUMBIUM	3.0 %	7440-03-1
ALUMINUM	3.0 %	7429-90-5
SILICON	2.0 %	7440-21-3

This product contains hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains materials that are acute, chronic hazards.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:

Flush eye with water for 15 minutes.

SKIN CONTACT FIRST AID:

Contaminated clothing should be discarded in a manner which limits further exposure. Immediately wash skin with soap and plenty of water.

INHALATION FIRST AID:

Although this product is not known to cause respiratory problems, if breathing is difficult, remove to fresh air and provide oxygen.

INGESTION FIRST AID:

If swallowed, immediately give 2 glasses of water. Induce vomiting.



5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

COC Flash Point: N/A
Autoignition Temperature: N/A

FLAMMABLE LIMITS IN AIR

LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA:

Use dry sand or earth to smother fire.

FIRE & EXPLOSION HAZARDS:

No known unusual hazards in a fire/explosion situation.

FIRE FIGHTING INSTRUCTIONS:

Avoid breathing smoke, fumes, and decomposition products. As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):

Wear appropriate personal protective equipment.

LARGE SPILLS PROCEDURE:

Contain spilled material.

SMALL SPILLS PROCEDURE:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

Wash thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Store in a cool dry area.

STORAGE PRECAUTIONS:

Store in a cool dry place.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

If user operations generate dust, fume, or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

EYE / FACE PROTECTION REQUIREMENTS:

Chemical goggles are recommended to avoid contact with eyes.

SKIN PROTECTION REQUIREMENTS:

Wear protective gloves to minimize skin contamination. Wash hands thoroughly after handling.

RESPIRATORY PROTECTION REQUIREMENTS:

Atmospheric levels should be maintained below the exposure guideline.

EXPOSURE GUIDELINES:

NICKEL

OSHA PEL: 1 mg/m³

OSHA TWA: 1 mg/m³

CHROMIUM

OSHA PEL: 1 mg/m³

OSHA TWA: 1 mg/m³

MOLYBDENUM

OSHA PEL: 10 mg/m³

OSHA TWA: 5 mg/m³

ALUMINUM

OSHA PEL: 10 mg/m³

OSHA TWA: 10 mg/m³

SILICON

OSHA PEL: 10 mg/m³

OSHA TWA: 10 mg/m³

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM : Solid
COLOR . . . : Metallic Grey
ODOR : No odor

10. STABILITY AND REACTIVITY

STABILITY:

Stable.

POLYMERIZATION:

Product will not undergo polymerization.



(section 10 continued)

INCOMPATIBILITY WITH OTHER MATERIALS:

Decomposition will not occur if handled and stored properly.

11. TOXICOLOGICAL INFORMATION

CHRONIC EFFECTS /:

May cause respiratory disease.

12. ECOLOGICAL INFORMATION

MISCELLANEOUS:

No information available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

14. TRANSPORT INFORMATION

PRODUCT LABEL ...: BF C&B Alloy


15. REGULATORY INFORMATION

REGULATORY LISTS SEARCHED:

01 = SARA 313	02 = CA Proposition 65
03 = SARA 302 / 304	04 = CERCLA 302.4
05 = ACGIH TWA	06 = ACGIH STEL
07 = ACGIH CALC TLV	08 = OSHA PEL
09 = CANADIAN WHMIS	10 = OSHA Ceiling

EEC Symbols and Indications of Danger:

Irritant (Xi)



(section 15 continued)

R-Phrases:


R36/37/38 - Irritating to eyes, respiratory system, and skin.
R43 - May cause sensitization by skin contact.

S-Phrases:

None

WHMIS Hazard Symbols:

Class D2 - Materials Causing Other Toxic Effects



Canadian Disclosure List

NICKEL (7440-02-0)
CHROMIUM (7440-47-3)
MOLYBDENUM (7439-98-7)
ALUMINUM (7429-90-5)

SARA Title III - Section 313

NICKEL (7440-02-0)
CHROMIUM (7440-47-3)
ALUMINUM (7429-90-5)

CERCLA Hazardous Substances

NICKEL (7440-02-0) -- RQ 100 lb
CHROMIUM (7440-47-3) -- RQ 5000 lb

RCRA Hazardous Substances

NICKEL (7440-02-0) -- RCRA Code: Unknown
CHROMIUM (7440-47-3) -- RCRA Code: D007

Title V

NICKEL (7440-02-0)
CHROMIUM (7440-47-3)
MOLYBDENUM (7439-98-7)
ALUMINUM (7429-90-5)

CA Proposition 65

NICKEL (7440-02-0)

SC Toxic Air Pollutants List

NICKEL (7440-02-0)



(section 15 continued)

MISCELLANEOUS INFORMATION:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

16. OTHER INFORMATION

REASON FOR ISSUE ...: New MSDS
PREPARED BY: Phyll Tabone
APPROVED BY: John Nicpon
TITLE: Quality Manager
APPROVAL DATE: May 5, 2009
SUPERCEDES DATE: May 5, 2009
RTN NUMBER: 00002056 (Official Copy)

ABBREVIATIONS USED IN THIS MSDS:

TLV - THRESHOLD LIMIT VALUE	TWA - TIME WEIGHTED AVERAGE
STEL - SHORT TERM EXPOSURE LIMIT	TPQ - THRESHOLD PLANNING QUANTITY
RQ - REPORTABLE QUANTITY	PEL - PERMISSIBLE EXPOSURE LIMIT
C - CEILING LIMIT	CAS - CHEMICAL ABSTRACT SERVICE NUMBER
NDA - NO DATA AVAILABLE	N/A - NOT APPLICABLE OR NOT AVAILABLE

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of CMP Industries LLC. The data on this sheet are related only to the specific material designated herein. CMP Industries LLC assumes no legal responsibility for use or reliance upon these data.

END OF MSDS

